

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 669
IDENTITY: BREAK DOWN

Revision Date: 06/24/2004

Section I

Manufacturer's Name: PRO-PLANET Industrial Supply
Address: 1615 Monrovia Ave.
Costa Mesa
State: CA Zip Code: 92627

Telephone Numbers:
Emergency: 800/535-5053
Information: 949/645-4582

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include D-LIMONENE, ISOPARAFINIC HYDROCARBON, ISOPROPYL ALCOHOL, and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 362 Specific Gravity (water=1) 0.09
Vapor Pressure (mm Hg) 1 Melting Point: N/A
Vapor Density (AIR=1) 1 Evaporation Rate: <1
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: BROWN JELLED LIQUID, AROMATIC SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >150F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES > 120 F MAY CAUSE BURSTING.

