

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 624
IDENTITY: RITE AWAY **16A** **Revision Date: 05/19/2004**

Section I

Manufacturer's Name: PRO- PLANET INDUSTRIAL SPLY *** **Telephone Numbers:**
Address: 1615 MONROVIA AVE. **Emergency:**
800/535- 5053
COSTA MESA **Information:**
State: CA Zip Code: 92627 **949/645- 4582**

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: 1

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
1, 8- P- MENTHADIENE	5989- 27- 5	NE	NE	N/A	_____
ACETONE	67- 64- 1	1000 PPM	750 PPM	N/A	_____
GLYCOL ETHER DPM	34590- 94- 8	ND	ND		_____
GLYCOL ETHER PM	107- 98- 2	NE	100 PPM	N/A	_____
PROPANE/N- BUTANE	68476- 86- 8	1000 PPM	600 PPM	N/A	_____
XYLENE(XYLOL) *	1330- 20- 7	100 PPM	100 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO- KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point: 165 **Specific Gravity (water=1) 1.00**
Vapor Pressure(mm Hg) 100 **Melting Point: N/A**
Vapor Density(AIR=1) >1 **Evaporation Rate: 2**
Solubility in Water: 0% **(Butyl Acetate=1)**
Appearance and Odor: VISCOUS SPRAY, AEROMATIC SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): 100F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 624

Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): PLASTICS, PRE-TEST TO BE SPRAYED
BEFORE USING.
Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY
PRODUCE PHOSGENE, CARBON MONOXIDE AND HYDROGEN CHLORIDE GASES.
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards(Acute and Chronic):
INHALATION: WILL CAUSE DIZZINESS IF INHALED DIRECTLY. EYES: MAY CAUSE
TEMPORARY CORNEAL OPACITY. WILL CAUSE SEVERE IRRITATION. SKIN: MAY CAUSE
LOCALIZED DEFATTING OF SKIN AND IRRITATION. INGESTION: SEE BELOW
Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO
Signs and Symptoms of Exposure: INGESTION: MAY CAUSE NAUSEA, VOMITING,
DIARRHEA AND RESTLESSNESS. ASPIRATION INTO THE LUNGS CAN CAUSE SEVERE
CHEMICAL PNEUMONITIS OR PULMONARY HEMORRHAGE, WHICH CAN BE FATAL.
Medical Conditions Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:
FLUSH WITH WATER FOR 15 MINUTES & CONTACT PHYSICIAN. SKIN: WASH WITH SOAP
& WATER. TREAT AFFECTED AREAS WITH SKIN MOISTURIZER & CONTACT PHYSICIAN.
INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE AN ABSORBENT CLAY MATERIAL OR TOWEL. DISPOSE OF RESIDUE IN
ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: WRAP CONTAINER IN OLD NEWSPAPER AND PLACE IN TRASH
COLLECTION. DO NOT REUSE EMPTY CONTAINER.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT, SPARKS, FIRE OR OPEN FLAME.

Other Precautions: EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
DO NOT PUNCTURE OR INCINERATE CONTAINER. VAPOR MAY COLLECT IN LOW LYING
AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA.
Ventilation: Local Exhaust: UNDER NORMAL USE ALL THAT IS GENERALLY REQUIRED.
Mechanical: REQUIRED IF TLV IS TO BE EX Special: NOT NORMALLY REQUIRED.
Other: NONE
Protective Gloves: CHEMICAL RESISTANT IF OVEREXPOSURE IS LIKELY.
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
NORMALLY NOT REQUIRED.
Work/Hygiene Practices:
WASH HANDS AFTER USE.