

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 606
IDENTITY: SHOOT DOWN

Revision Date: 02/27/2004

Section I

EPA Registration No: 44446-54

Manufacturer's Name: PRO-PLANET Industrial Supply

Address: 1615 Monrovia Ave
Costa Mesa

State: CA Zip Code: 92627

Telephone Numbers:

Emergency:
800/535-5053

Information:
949/645-4582

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 2 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Name Cas No. OSHA PEL ACGIH TLV OTHER LIM %

CARBON DIOXIDE 124-38-9 5000 PPM 5000 PPM N/A
ISOPARAFINIC HYDROCARBON 64742-47-8 400 PPM 400 PPM

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 232 C Specific Gravity (water=1) 0.81
Vapor Pressure (mm Hg) .4 Melting Point: N/A
Vapor Density (AIR=1) 6.2 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, CHARACTERISTIC INSECTICIDE, SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >165F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CAUTION: CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

